

Please Read! It is very important to us at DOWCO Inc. that you, our customer, read and understand these installation instructions. If while reading these instructions you are unsure about securing the bag please contact us at 1-800-558-7755.

**⚠ WARNING**

- This luggage is recommended for use with a sissy bar/backrest and luggage rack combination which is permanently attached to the motor-cycle. Mount the bag at this location ONLY.
- Do not exceed the manufacturer's recommended load capacity of the luggage rack or motorcycle.
- Consult your owner's manual for tire inflation pressures and gross axle weight rating. Failure to follow recommended weight loading capacities may affect handling. This may result in injury or property damage.
- Secure the bag to the vehicle so the bag will not shift during operation.
- Verify that straps do not obstruct reflectors, turn signals, or tail lamp.
- Verify that mounting straps will not contact rear wheel during operation.
- The bag's extendable pull handle must be fully retracted before operation of the vehicle.

Installation Instructions:

1. Open and loosen the (2) hook & loop straps on the back side of the luggage, and lower the bag onto the luggage rack with those straps going around the sissy bar/backrest.
2. Be sure the bag is centered and sitting firmly on the luggage rack and tighten the hook and loop straps around the backrest. Close (fasten) the hook & loop straps to secure the bag (see Fig. 1).



3. Locate the zippers on either side at the bottom of the bag. Open them and pull out the two short straps with buckles (see Fig. 2). Also locate the mounting strap kit included with the bag. Connect the long mounting straps to the short straps that are attached to the bag. These straps use side release buckles to offer quick attachment and release.



4. Loop the long mounting straps (on both sides of the bag) around the directional indicator bar (or similar sturdy mounting area), and connect the final side release buckles (see Fig. 3). Be sure the buckle has "snapped" into place, and the connection is secure.

5. Pull the slack out of the loose end of the strap to tighten. Excess strap material should be knotted or cut off.

**⚠ WARNING**

Allowing straps to hang loose may cause damage to packs and/or painted finishes. Hanging straps may become entangled in the wheel or chain.

## Roller Bag Features:

- Accessory Holding Front Door  
(Fig 4.)



- Extendable Pull Handle  
(Fig. 5)



- Side Mounted Net Pocket  
(Figs. 6 & 7)

Both sides of the bag are expandable to allow the use of two net pockets located within the zippered side panels. To use, unzip and expand the side panel, which will expose a second, double pull zipper that will permit access to the two pockets. Make certain that the side panel is properly closed prior to operation of the vehicle.



## ⚠ WARNING

When using one or more of the side panel net pockets, make certain that the load is properly balanced on both sides of the bag to prevent unwanted shifting during vehicle operation.

- Built in Rain Cover(not pictured)

The bag is equipped with a built in rain cover, enclosed in a zippered storage pocket located on the top front of the bag.

1. Unzip the storage pocket and completely pull out the rain cover. Note: The rain cover is attached to the pocket by a wide elastic strap.
2. Unroll the rain cover and pull it down over the luggage bag. An elastic band sewn into the opening of the cover secures it snugly around the bottom of the bag. Make certain that the cover goes over the sissy bar/backrest as well as the hook and loop mounting straps.

**Care & Cleaning:** Use mild household detergent and soft brush to remove dirt or road grime. Rinse thoroughly and dry before using. Do not put in washer or dryer, dry cleaning is not recommended.

**Note: Do not store Rain Cover when wet!**